



Available in / Verfügbar in

- PPCM-50
- PPCM-80
- PPCM-100
- PPCM-150

Models with bigger dimensions / tonnages are available on request (these are not standard)

Modelle mit größeren Abmessungen / Tonnagen sind auf Anfrage erhältlich (nicht Standard)



These C-frame presses of RHTC consist of an electro welded structure made out of S355JR steel and are designed for stamping, die-cutting and forming / to incorporate in automated production lines. Made in Europe.



Die hydraulischen C-Rahmen-Pressen von RHTC haben eine elektrisch geschweißte Konstruktion, die ausschließlich aus Stahl der Güte S355JR hergestellt wird und sind insbesondere dafür geeignet Arbeiten wie Prägen, Tiefziehen und Stanzen zu erbringen und in automatisierte Fertigungslinien integriert zu werden. Hergestellt in Europa.

SPECIFICATIONS / TECHNISCHE DATEN		PPCM-50	PPCM-80	PPCM-100	PPCM-150
Force / Kraft	[tn]	50	80	100	150
Motor power / Motorleistung	[kw]	4	5.5	7.5	7.5
Throat depth / Ausladung	[mm]	265	290	325	375
Working speed / Arbeitsgeschwindigkeit	[mm/sec]	6.3	6	6.2	3.9
Approaching speed / Annäherungsgeschwindigkeit	[mm/sec]	32	25	31	20
Return speed / Rücklaufgeschwindigkeit	[mm/sec]	42	36	48	31
Maximum pressure / Höchstdruck	[bar]	320	320	320	320
Piston stroke / Kolbenhub	[mm]	250	250	250	250
Guides diameter / Durchmesser Führungen	[mm]	50	50	50	50
Lower table size / Unterer Tischgröße	[mm]	700 x 450	700 x 500	800 x 550	900 x 650
Upper table size / Oberer Tischgröße	[mm]	550 x 300	600 x 350	650 x 400	700 x 450
Max. vertical light / Lichte Höhe	[mm]	400	400	400	400
Working height / Arbeitshöhe	[mm]	850	850	900	950
Total length (lateral) / Gesamttiefe	[mm]	1290	1460	1590	1750
Total width (frontal) / Gesamtbreite	[mm]	1160	1210	1240	1330
Total height / Gesamthöhe	[mm]	2085	2090	2250	2395
Weight / Gewicht	[kg]	1750	2350	3150	4700