



HARRISON

Alpha 1550S x 2000mm CNC Gap Bed Lathe Year 2004

Stock No 29354

| | |
|---------------------------|------------------------------|
| Swing over bed | 554 mm |
| Swing over cross slide | 370 mm |
| Swing in gap | 830 mm |
| Dist. between centres | 2000 mm |
| Spindle bore | 104 mm |
| Spindle nose | Camlock D1-11 |
| Spindle speeds (3 ranges) | 18-200, 55-605, 140-1800 rpm |
| Main motor | 11 kW |
| Manual feedrates X/Z | 0.03 -0.06 mm/rev |
| CNC feedrates X/Z | 0-5750 mm/min |
| Rapids guards open | 2000mm/4000mm |
| Rapids guards closed | 3000mm/6000mm |
| Tailstock quill dia. | 95 mm |
| Quill travel | 310 mm |
| Tailstock | 6MT |

Options/Additional Equipment

Quick change toolpost with 5 x toolholders

400mm dia. 4 jaw chuck

400mm dia. 3 jaw chuck with 2 sets of internal/external jaws

240mm dia. 3 point roller steady

Coolant pump & 100 litre capacity tank

Auto Auto-lube

Chuck guard

GE Fanuc Alpha 1000 Series CNC Control

| | |
|------------------------------|-----------------------|
| Machine dimensions L x W x H | 4190 x 1675 x 1778 mm |
|------------------------------|-----------------------|

| | |
|----------------|---------|
| Machine weight | 3350 kg |
|----------------|---------|

Barry Street Works
Barry Street
Oldham
Greater Manchester
ENGLAND
OL1 3NE

t: +44 (0) 161 633 8880

e: info@gmmachinery.com

Descriptions and dimensions are given in good faith however these are not guaranteed and prospective purchasers are advised to check any vital information themselves. GM Machinery Ltd will not be held responsible for any mis-description.

In accordance with Health & Safety at Work Act 1974 this machine must be fitted with guards and it is condition of sale that the purchaser accepts full responsibility to ensure that suitable guards are fitted in order to comply in full with this act.